

FLOS

In Vitro Bollard 3 , 335.4" - 900mm Black 11W, 1150lm, 2700K, CRI 80 Integral Not dimmable LED driver UL - Specification Sheet by Philippe Starck, 2020

Mounting	Base on Ground
Lamp (Bulb) Description	LED 11W, 1150lm, 2700K, CRI 80
Canopy Dimension	667
Environment	Outdoor - Wet location
Dimming	Not dimmable
Finish	Black

Technical and Product Description Lighting outdoor collection with diffuse light for exterior ground installation. Integral opalescent diffuser and external protection in transparent borosilicate glass. The structure is made of die-cast and extruded aluminum treated with a chemical conversion process for effective resistance to atmospheric agents.


The body is powder coated and comes in various finishes. Integrated LED light source with Edge Lighting optical technology to guarantee perfect uniform lighting. Integrated 120V ON/OFF or dimmable electrical power supply.

The unit comes with a watertight plug for connection to the electrical network. The device may be installed on any flooring with anchors. Box for installation on flooring laid over concrete to be order separately



● F018A23AU30 Black

Dimensional Image



IN VITRO BOLLARD
35.4" / 900MM

Electrical

Voltage	120-277
IP Rating	IP65

Physical

Supply	LED driver
Construction Material	Aluminum, Glass
Weight	4.4 lbs

Certifications



Other options:

FINISH: * Anthracite Black

Dark Brown

Forest Green

Pale Green Terracotta

White

TEMP:

DIMMING PROTOCOL:

