

FLOS

Smithfield S LED - 2700K, White - Specification Sheet by Jasper Morrison, 2009

Mounting	Ceiling Pendant
Lamp (Bulb) Description	108 x LED 30W 2700K 2791lm CRI90
Environment	Indoor - Dry Location
Dimming	0-10V (120Vac or 277Vac) or ELV (120Vac Only) or Triac (120Vac Only)
Finish	White
Technical and Product Description	SMITHFIELD S suspension lamp with direct light. Aluminum body. Available in gloss black, Matte Black, white or mud. Injection-moulded opalescent polycarbonate diffuser. Steel ceiling attachment with steel suspension cable. Three-pole electric cable in PTFE double insulation. Inquire about a 3500K option.

Electrical

IP Rating	IP20
-----------	------


Physical

Cord Length (inches)	106" - Clear
Construction Material	Aluminum, Polycarbonate
Weight	11 lbs



○ FU136709 White

Dimensional Image



Certifications



Other available finish and lamping options:

FINISH:

<input type="radio"/> Black	<input type="radio"/> Green
<input type="radio"/> Matte Black	<input type="radio"/> Mud
<input type="radio"/> Red	<input checked="" type="radio"/> White

LAMP SOURCE:

<input type="radio"/> E26	<input type="radio"/> Halogen
<input checked="" type="radio"/> LED 2700K	<input type="radio"/> LED 3000K

*