

Plat Surface

Typology: Pendant

Designed by: Nahtrang Design

Pendant Plat Surface LED 13 SW 2700-3000-4000K PHASE CUT/O-10V/ELV Black 805lm

Plat steals the show without aiming to be the center of attention, given its traditionally blown glass in soft tones.

Technical features

Lampholder: LED

Total power consumption of light (W): 13

Delivered lumens: 805 (3000K)

Correlated Colour Temperature (CCT):
SW 2700-3000-4000K

Lens / Reflector Angle: FLOOD 89°

Structure Material: Steel

Structure Finish: Black

Diffuser Material: Glass

Diffuser Finish: Green

Voltage / Frequency: 120-277V/60Hz

Useful life: 50,000h L80B20

Dimming protocol: PHASE CUT/O-10V/ELV

Warranty: 5 years

Easily recyclable luminaire

Lampholder	Quantity	Light source power (W)
LED	1	10.5W

Logistics

Net weight (lb): 6

Packaged weight (lb): 14

Packaging (in): 18 7/8" x 18 7/8" x 16"

DRY CRI90



Images do not show North American backplate

Export date: 10/07/23

Leds-C4 Afores S/N 25750 Torà (Lleida) Spain +34 973 468 100
Bover USA 1231 Coller Rd, NW Atlanta, GA 30318 +1 404 924 2342