


ZIRKOL – C

ZIRKOL – C is a family of circular suspension lamps suitable for general and decorative lighting.

Anodized aluminium body and opal screen for a homogeneous lighting.

Available as single direct light emission version with high flux and different colour temperatures.

Driver and dimmer interface included



HOME 39.4" | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	45W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	2700K
Luminous flux	2616lm
Typ CRI	90
IP class	IP40
Dimensions	ø39.4x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled.

Codes

UZRC1610G15DBO
 UZRC1610G15DNE
 UZRC1610G15DOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 39.4" | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	45W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	3000K
Luminous flux	2769lm
Typ CRI	90
IP class	40
Dimensions	ø39.4x1.9
Materials	Aluminum
Notes	

Round canopy with 1 x driver WALIMLED100/24 | 1 x dimmer interface WDIMDALIHP | 1 x electrical cable 13.1' | 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black | RAL 9016 white | shipped assembled.

Codes

UZRC1610G15WBO
 UZRC1610G15WNE
 UZRC1610G15WOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 39.4" | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	45W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	4000K
Luminous flux	3077lm
Typ CRI	90
IP class	IP40
Dimensions	ø39.4x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled.

Codes

UZRC1610G15NBO
 UZRC1610G15NNE
 UZRC1610G15NOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 39.4" | UP-DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	90W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	2700K
Luminous flux	5231lm
Typ CRI	90
IP class	IP40
Dimensions	ø39.4x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled

Codes

UZRC1710G15DBO
 UZRC1710G15DNE
 UZRC1710G15DOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 39.4" | UP-DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	90W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	3000K
Luminous flux	5539lm
Typ CRI	90
IP class	IP40
Dimensions	ø39.4x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled

Codes

UZRC1710G15WBO
 UZRC1710G15WNE
 UZRC1710G15WOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 39.4" | UP-DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	90W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	4000K
Luminous flux	6154lm
Typ CRI	90
IP class	IP40
Dimensions	ø39.4x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled

Codes

UZRC1710G15NBO
UZRC1710G15NNE
UZRC1710G15NOR


Structure

matt white
matt black
matt gold

Certificazioni




CIRCLE HOME 39.4"




| Ø 39.4 |

CIRCLE HOME 59"



| Ø 59 |

CIRCLE 78.7



| Ø 78.7 |

HOME 59" | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	68W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	2700K
Luminous flux	3923lm
Typ CRI	90
IP class	IP40
Dimensions	ø59x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled

Codes

UZRC1615G15DBO
 UZRC1615G15DNE
 UZRC1615G15DOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 59" | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	68W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	3000K
Luminous flux	4154lm
Typ CRI	90
IP class	IP40
Dimensions	ø59x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled

Codes

UZRC1615G15WBO
 UZRC1615G15WNE
 UZRC1615G15WOR


Structure

matt white
 matt black
 matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 59" | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	68W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	4000K
Luminous flux	4616lm
Typ CRI	90
IP class	IP40
Dimensions	ø59x1.9
Materials	Aluminum
Notes	Round canopy with 1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 13.1' 3 x adjustable metal cable (length from 9.8' to 0,16.4') (including ceiling attachment). RAL 9005 black RAL 9016 white shipped assembled

Codes

UZRC1615G15NBO
UZRC1615G15NNE
UZRC1615G15NOR


Structure

matt white
matt black
matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 78.7" | DOWNLIGHT - 2700K

LAMPING

Source	Linear LED
Total power	90W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	2700K
Typ CRI	90
IP class	IP40
Dimensions	ø78.7x1.9
Materials	Aluminum
Notes	1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 16.4' 4 x adjustable metal cable length 9.8' (including ceiling attachment). Remote driver RAL 9005 black RAL 9016 white shipped in 2 pieces

Codes

UZRC1620G15DBO
UZRC1620G15DNE
UZRC1620G15DOR


Structure

matt white
matt black
matt gold


Certificazioni



CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 78.7" | DOWNLIGHT - 3000K

LAMPING

Source	Linear LED
Total power	90W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	3000K
Luminous flux	5539lm
Typ CRI	90
IP class	IP40
Dimensions	ø78.7x1.9
Materials	Aluminum
Notes	1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 16.4' 4 x adjustable metal cable length 9.8' (including ceiling attachment). Remote driver RAL 9005 black RAL 9016 white shipped in 2 pieces

Codes

UZRC1620G15WBO
UZRC1620G15WNE
UZRC1620G15WOR


Structure

matt white
matt black
matt gold


Certificazioni




CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7



HOME 78.7" | DOWNLIGHT - 4000K

LAMPING

Source	Linear LED
Total power	90W
Emission	Diffused orientable
Switching	DALI 1-100%
Tension	110/240V
Color temperature	4000K
Luminous flux	6154lm
Typ CRI	90
IP class	IP40
Dimensions	ø78.7x1.9
Materials	Aluminum
Notes	1 x driver WALIMLED100/24 1 x dimmer interface WDIMDALIHP 1 x electrical cable 16.4' 4 x adjustable metal cable length 9.8' (including ceiling attachment). Remote driver RAL 9005 black RAL 9016 white shipped in 2 pieces

Codes

UZRC1620G15NBO
UZRC1620G15NNE
UZRC1620G15NOR


Structure

matt white
matt black
matt gold


Certificazioni



CIRCLE HOME 39.4"



CIRCLE HOME 59"



CIRCLE 78.7

