

North

Design by Arik Levy.

Reference

5670.

Application

Pendants

Installation type

Surface mounted

Description

North pendant light designed by Arik Levy. A lacquered aluminum shade with a white interior holds the LED light source while suspended by a black cable. A round steel canopy matches the finish of the shade. Available in charcoal gray, matte beige or matte white lacquer.

Diffuser

Acrylic diffuser

Materials

Cane: Carbon fiber

Shade: Aluminum

Canopy: Steel

Diffuser: Acrylic

Finishes



5670-10 White (NCS S 0300-N)




5670-11 Black (NCS S 8500N)



5670-24 Cream (NCS S 2005-Y50R)

Sketch



Electrical characteristics

1 x LED 9W 350mA

Total 9.0 W



VIBIA



Light source: 2700K CRI >80 1041 lm 116 lm/W

Fixture: 766.49 lm 85.16 lm/W

Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI

Technical characteristics

- Cable can be adjusted in the field. 157" max.


Installation and assembly

Please see the installation manual

Light distribution

General lighting - opaque shade

Fixture suitable for general ambient illumination, distributing light mainly upward and/or downward.



Photometric data

Certificates



North

Design by Arik Levy.

VIBIA

Reference

5672.

Application

Pendants

Installation type

Surface mounted

Description

North pendant light designed by Arik Levy. A lacquered aluminum shade with a white interior holds the LED light source while suspended by a black cable. A round steel canopy matches the finish of the shade. Available in charcoal gray, matte beige or matte white lacquer.

Diffuser

Acrylic diffuser

Materials

Shade: Aluminum
Canopy: Steel
Cane: Carbon fiber
Diffuser: Acrylic

Finishes



5672-10 White (NCS S 0300-N)




5672-11 Black (NCS S 8500N)



5672-24 Cream (NCS S 2005-Y50R)

Sketch



Electrical characteristics

1 x LED 9W 350mA

Total 9.0 W



Light source: 2700K CRI >80 1041 lm 116 lm/W

Fixture: 757.94 lm 84.21 lm/W

Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI

Technical characteristics

- Cable can be adjusted in the field. 157" max.


Installation and assembly

Please see the installation manual

Light distribution

General lighting - opaque shade

Fixture suitable for general ambient illumination, distributing light mainly upward and/or downward.



Photometric data

Certificates



North

Design by Arik Levy.

VIBIA

Reference

5674.

Application

Pendants

Installation type

Surface mounted

Description

North pendant light designed by Arik Levy. A lacquered aluminum shade with a white interior holds the LED light source while suspended by a black cable. A round steel canopy matches the finish of the shade. Available in charcoal gray, matte beige or matte white lacquer.

Diffuser

Acrylic diffuser

Materials

Shade: Aluminum
Canopy: Steel
Cane: Carbon fiber
Diffuser: Acrylic

Finishes



5674-10 White (NCS S 0300-N)




5674-11 Black (NCS S 8500N)



5674-24 Cream (NCS S 2005-Y50R)

Sketch



Light source: 2700K CRI >80 1041 lm 116 lm/W

Fixture: 830.69 lm 92.29 lm/W

Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI

Technical characteristics

- Cable can be adjusted in the field. 157" max.


Installation and assembly

Please see the installation manual

Light distribution

General lighting - opaque shade

Fixture suitable for general ambient illumination, distributing light mainly upward and/or downward.



Photometric data

Certificates



Electrical characteristics

1 x LED 9W 350mA

Total 9.0 W

