

Palma

Design by Antoni Arola.

Reference

3728.

Application

Pendants

Installation type

Surface mounted

Description

Fusing technology, space, and architecture, Sticks offers a creative lighting toolkit for integrating light elements in an interior space. Pure and graphic, the minimalist aluminium rods transform linear light into a floating sculpture.

Diffuser

Blown-glass diffuser

Materials

Profile: Aluminum

Flowerpot: PMMA (thermoplastic polymer)

Ring: Aluminum

Wall plate: Steel

Finishes




3728-18 Graphite (ADAPTA RF 9913 WX)



3728-93 White (RAL 9016)

Sketch



Electrical characteristics

4 x LED 4.6W 500mA

Total 18.4 W



VIBIA



Light source: 2700K CRI >90 1736 lm 94.34 lm/W

Fixture: 1371 lm 74.51 lm/W

Driver included: CC - Constant Current 500 mA 120~277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or Lutron ECO

Technical characteristics

- Cable can be adjusted in the field. 157" max.

- Plants not included


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Coordinate system : CG

Isolux : Isolux (Floor)

Maximum value : 147.39 cd/klm

Light position :

Light position : C=0.00 G=0.00

X=0.00m Y=0.00m Z=2.50m

Symmetry on the planes : Double symmetrical

Certificates




425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305
404.876.1064 sales@illumco.com