

# Tempo

Design by Lieve Altherr.

## Reference

**5757.**

## Application

Wall Fixtures

## Installation type

Recessed

## Description

Wall lamp. An adjustable rod emerges from the base attached to the wall, with blown glass diffuser and a tensing cable that permits precise adjustment of the height of the glass tulip. Connection without a plug. LED light source.

## Diffuser

Blown-glass diffuser

## Materials

Body: Steel  
Diffuser: Blown-glass  
LED support: Aluminum

## Finishes



**5757-18** Graphite (ADAPTA RF 9913 WX)




**5757-35** Brick (NCS S 4040-Y70R)



**5757-62** Green (NCS S 3010-G20Y)

## Sketch



## Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



# VIBIA



**Light source:** 2700K CRI >90 440.81 lm 110 lm/W

**Fixture:** 301.62 lm 75.4 lm/W

**Driver included:** CC - Constant Current 350 mA 120~277V 50/60Hz

**Electronic dimming:** 0-10V

**Optional dimming:** DALI or TRIAC

## Technical characteristics

- Recessed


## Installation and assembly

Please see the installation manual

## Light distribution

### General lighting

Lamp for general lighting that equally distributes the light in all directions.



## Photometric data

Efficiency : 100%

Coordinate system : CG

Total flux : 301.62 lm

Maximum value : 235.37 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

## Certificates



 **illuminaitions**  
425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305  
404.876.1064 sales@illumco.com