

Tempo

Design by Liovore Altherr.

Reference

5767.

Application

Wall Fixtures

Installation type

Recessed

Description

Wall lamp composed of a stylized profile attached to the wall and topped by a blown glass diffuser that gives the piece a delicate image. Connection without a plug. LED light source.

Diffuser

Blown-glass diffuser

Materials

Body: Steel

Diffuser: Blown-glass

LED support: Aluminum

Finishes



5767-18 Graphite (ADAPTA RF 9913 WX)




5767-35 Brick (NCS S 4040-Y70R)



5767-62 Green (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA



Light source: 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 302.04 lm 75.4 lm/W

Driver included: CC - Constant Current 350 mA 120~277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or TRIAC

Technical characteristics

- Recessed


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 100%

Coordinate system : CG

Total flux : 302.04 lm

Maximum value : 203.44 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates




425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305
404.876.1064 sales@illumco.com