

Wireflow

Design by Arik Levy.

VIBIA

Reference

0338.

Application

Pendants

Installation type

Surface mounted

Description

The Wireflow lineal pendant lights have two new patterns. Their appearance, as a structure of fine cables finished with six black lacquered aluminum LED terminals, is ideal for discretely providing accent illumination above a variety of areas and spaces for a look ranging from eclectic to futuristic.

Diffuser

Polycarbonate diffuser

Materials

Diffuser: Polycarbonate

Body: Aluminum

Horizontal rods: Steel


Canopy: Steel

Finishes



0338-04 Black (RAL 9005)

Sketch



Electrical characteristics

6 x LED 4.5W 700mA

Total 27.0 W



A+



Light source: 2700K CRI >80 2941.56 lm 109 lm/W

Fixture: 1179.62 lm 43.68 lm/W

Driver included: CC - Constant Current 700 mA 120~277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI

Technical characteristics

- Cable can be adjusted in the field. 157" max.


Installation and assembly

Please see the installation manual

Light distribution

Highlight

Lamp used to highlight a specific element.



Photometric data

Efficiency : 40.10%

Coordinate system : CG

Total flux : 2941.60 lm

Maximum value : 55.38 cd/klm

Light position : C=50.00 G=50.00

Symmetry on the planes : Double symmetrical

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

