

TALO LED wall

TALO 60 (24") wall




EMISSION
indirect and direct

LIGHT SOURCE
LED
36W 3000K >80CRI

DIMMING FEATURE
dimmable

DIMENSIONS



FINISH

- gloss white
- polished aluminum
- satin copper

CERTIFICATIONS
c.UL.us listed, ADA

TALO 90 (36") wall




EMISSION
indirect and direct

LIGHT SOURCE
LED
39W 3000K >80CRI

DIMMING FEATURE
dimmable

DIMENSIONS



FINISH

- white
- silver/grey

CERTIFICATIONS
c.UL.us listed, ADA

TALO 120 (48") wall




EMISSION
indirect and direct

LIGHT SOURCE
LED
54W 3000K >80CRI

DIMMING FEATURE
dimmable

DIMENSIONS



FINISH

- white
- silver/grey

CERTIFICATIONS
c.UL.us listed, ADA

TALO 150 (60") wall




EMISSION
indirect and direct

LIGHT SOURCE
LED
68W 3000K >80CRI

DIMMING FEATURE
dimmable

DIMENSIONS



FINISH

- white
- silver/grey

CERTIFICATIONS
c.UL.us listed, ADA

TALO MINI wall

TALO MINI LED wall



EMISSION

direct and indirect


LIGHT SOURCE

LED
20W 3000K >80CRI
or
20W 2700K >90 CRI

DIMMING FEATURE

dimnable

DIMENSIONS



FINISH

white
 silver/grey
 polished aluminum
 satin copper

CERTIFICATIONS

c.UL.us listed, ADA

TALO MINI HAL wall



EMISSION

direct and indirect


LIGHT SOURCE

HAL
max 150W R7s

DIMMING FEATURE

dimnable

DIMENSIONS



FINISH

white

CERTIFICATIONS

c.UL.us listed, ADA