


Tetragono wall

T417300W08

SPECIFICATIONS



Design By

Ernesto Gismondi

Collection

Outdoor



Specifications

Delivered lumens	434lm
Light output ratio	29.32lm/W
Power consumption	14.8W
Led type	14W Array*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>80
Life expectancy	50000Hrs
Control type	On/Off
Input Voltage	120V
Driver	MEAN WELL - 1 x APC-16-350
BUG Rating	B0-U3-G1

Colors & Finishes

■ Anthracite grey

Materials


- Lamp support in extruded aluminum
- Base in painted steel
- Lighting unit in die-cast aluminum
- Reflectors in metallic polycarbonate
- UV resistant diffuser in shock resistant polycarbonate

*Integrated light source

Features & Accessories

- Base contains holes for wall installation
- Provided with cable and IP67 connector
- Electronic driver integrated
- Standard non dimmable
- For dimming options, please consult with your Artemide Sales Representative

Dimensions




Packaging

1 Box

1 x 10-3/4" x 10-3/4" x 7-15/16" / 5.29 lbs - 27 cm x 27 cm x 20 cm / 2.4 kg

Light distribution

Diffused



Red = Max Cd. Through Vertical plane

Blue = Max Cd. Through Horizontal plane

Luminaire weight

3.97 lbs / 1.8 kg

Warranty

5 year limited warranty