
### FRAMEWORK - US FRAME G LED - technical sheet





#### **USFRAMEG**

Design by Manuel Vivian

Collection consisting of ceiling or wall lamps and suspended lamps in white aluminum.

Available in several sizes. The ceiling/wall lamps are also supplied in three different heights.

Typology: SUSPENSION

#### Ratings

- •Built in ED module
- •CCT 3000 K
- Uplight
- •Installs over 4 in. octagonal J-box (support independently)
- •Power supply 120/277V AC
- ·Switch mode: on-off
- •Dimmable 0-10V LED driver
- Extruded aluminum profile, painted
- Linear prismatic diffuser

Product code composition

12 x 12 cm — 4 3/4" x 4 3/4" thick 0.3 cm - 1/8" max 300 cm - 118 1/8

lb 18.07 ft3 14.48

cover plate: 12 x 12 cm - 4 3/4" x 4 3/4" thick 0.3 cm - 1/8" 35 3/8" - mo 06

186 cm - 73 1/4"

### **FRAMEWORK**

Туре	Article	Colours	Code End	Source	9
US	FRAME G LED	BC white	xx	LED	100.8W - 120-277V included diffused beam - 3000K

DRY LOCATION CRISO 🚟 US FRAMEGLED BC example composition code

LED 13236 lm 131 lm/W

XX

#### Available colors



ВС Wrinkled white aluminium

CUSTOMER

**NOTES** 

USFRAMEGLED BCXX

Luminous flux for all LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the

425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305 404.876.1064 sales@illumco.com

## FRAMEWORK - US FRAME M LED - technical sheet





#### **USFRAMEM**

### Design by Manuel Vivian

Collection consisting of ceiling or wall lamps and suspended lamps in white aluminum.

Available in several sizes. The ceiling/wall lamps are also supplied in three different heights.

Typology: SUSPENSION


#### Ratings

- •Built in **LED** module
- •CCT 3000 K
- Uplight
- •Installs over 4 in. octagonal J-box (support independently)
- •Power supply 120/277V AC
- •Switch mode: on-off
- •Dimmable 0-10V LED driver
- •Extruded aluminum profile, painted
- •Linear prismatic diffuser

lb 16.53 ft3 13.77

12 x 12 cm — 4 3/4" x 4 3/4" thick 0.3 cm - 1/8" 3 cm - 1 1/8" max 300 cm - 118 1/8"

cover plate: 12 x 12 cm - 4 3/4" x 4 3/4" thick 0.3 cm - 1/8"



127 cm - 50°

Product code composition

#### **FRAMEWORK**

Туре	Article	Colours	Code End	Source	2
US	FRAME M LED	BC white	xx	LED	67.2W - 120-277V included diffused beam - 3000K

e lotertek	4	DRY LOCATION	CRI80	dimmable 0-10V	LED	8824 lm	131 lm/W
examp	le com	position code   US	FRAMEMI	LED BC	XX		

Available colors



ВС Wrinkled white aluminium

CUSTOMER **NOTES** USFRAMEMLED\_\_\_BCXX

Luminous flux for all LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet

### FRAMEWORK - US FRAME P LED - technical sheet





lb 12.34 ft3 7.77

#### **USFRAMEP**

Design by Manuel Vivian

Collection consisting of ceiling or wall lamps and suspended lamps in white aluminum.

Available in several sizes. The ceiling/wall lamps are also supplied in three different heights.

Typology: SUSPENSION

#### Ratings

- •Built in LED module
- •CCT 3000 K
- •Uplight
- •Installs over 4 in. octagonal J-box (support independently)
- •Power supply 120/277V AC
- •Switch mode: on-off
- •Dimmable 0-10V LED driver
- •Extruded aluminum profile, painted
- ·Linear prismatic diffuser


Product code composition

### FRAMEWORK



ertek					0-10V	
amn	le com	nosition con	la IIIS	ERAMEDI	ED BC	Y

# 



#### Available colors



BC Wrinkled white aluminium

CUSTOMER\_\_\_\_\_NOTES\_\_\_\_USFRAMEPLED\_\_BCXX

Luminous flux for all LED luminaires is shown at source level.

Technical data could be subject to alteration without notice. Axo Light does not provide legal guarantee for the accuracy of this data sheet.

