## HOOPS - US HOOPS 2 - technical sheet



	lamps with interchangeat shapes and sizes. Gold o	eiling lamps and suspended ole elements in different or black finish. Built-in ce. The suspended lamps can ard.	Ratings •Built in line voltage ED module •CCT 3000 K •Downlight and uplight •Installs over 4 in. octagonal J-box •Power supply 120V AC •Switch mode: on-off, dimmable trailing edge •Metal frame
lb 12.57 ft <sup>3</sup> 15.185	Product code composition		
ی 0 15 cm - Ø 5 7/8" ن	HOOPS / DRIVER INCLUDED / with upward and downward lighting		
Ø 15 cm - Ø 5 7/8"	Type Article	Colours / Finish	Source
¢17.4 cm - 6 7/8"	US HOOPS 2	<b>OR</b> gold / <b>OR</b> gold	LED 2x17W - diffused beam 3000K
92 cm - 36 1/4 <sup>-</sup>		NE black/NE black	
intertek DRY LOCATION CRI90 - + TRAILING EDGE 120Vac LED 2660 Lr			dimmable ELV TRAILING EDGE 120Vac LED 2660 lm 78 lm/W PHASE CUT
80 cm - 31 1/2" 100 cm - 39 3/8"	example composition co	ode US HOOPS2 OR	OR LED
Available colors			
	CUSTOMER	NOTES	
USHOOPS2 LED			
Luminous flux for all built-in LED lun Technical data could be subject to a	ninaires is shown at source le Iteration without notice. Axo	evel. Light does not provide legal gu	Aarantee for the accuracy of this data sheet <b>Filluminations</b> 425 Peachtree Hills Ave. NE #3 Atlanta, GA 3030 404.876.1064 sales@illumco.co
			A - P (203) 730 0452 - F (203) 730 0460 rmation contact Axo Light USA