

Libri sconce reading light







1 2 5 2.25 0.5 25 Dimensions - 10.5" X 1.5" X 1.25" Aluminum (CM-006), polymer (CM-052), optional solid wood Product weight - 1 lb

Energy efficient LED light source Automatic ON/OFF when arm is pulled away from wall Light output - 160 lumens Light color - 2700 K (warm) Color accuracy - 90+ CRI LED power consumption - 2W Specifications subject to change


MATERIAL, FINISH & MOUNTING OPTIONS


Mounting kits are sold separately from the Libri fixture. No Mounting kit is required if the Libri fixture is to be installed using the Direct . Mount option.

Direct Mount Option is used when mounting directly to a headboard. There is no backplate and the cord must be fed through a hole in the headboard directly behind where the fxture is mounted and plugged into a wall outlet using the included AC adaptor.

J-Box Backplate is typically used when mounting a hardwired model to a junction box. It can also be mounted directly to a wall and used with a plugin model.

Wall Mount Plug In Backplate is used when mounting directly to the wall and plugging into a wall outlet. The wall mount is an elongated rectangle that allows the cord to exit discreetly below the fixture.





task light in a discrete and sturdy form that is very intuitive to use. Nick Sheridan, Designer





1751 MCGAW AVE, IRVINE, CA 92614