

The Plura is a simple, straight forward fixture that is excellently executed. With the Plura it was about resolving the seams and edges and their relationships to one another. The result is a scalable fixture that has a sharp, sophisticated feel.


Nick Sheridan Designer

dark stained

walnut (CM-002)



Plura flush mount



Dimensions:
Plura 18: 18" Ø, 7.8"
Plura 24: 24" Ø, 7.8"
Plura 30: 30" Ø, 9.8"
Plura 36: 36" Ø, 11.8"
Materials: solid wood, metal, polymer
Product weight:
Plura 18: 5 lb
Plura 24: 6 lb
Plura 30: 9 lb
Plura 36: 13 lb
Integrated LED Specifications
Integrated LED Specifications Light output:
,
Light output:
Light output: Plura 18 & 24: 1690 Lumens (source)
Light output: Plura 18 & 24: 1690 Lumens (source) Plura 30 & 36: 2815 Lumens (source)
Light output: Plura 18 & 24: 1690 Lumens (source) Plura 30 & 36: 2815 Lumens (source) Light color: 2700 K or 3500 K
Light output: Plura 18 & 24: 1690 Lumens (source) Plura 30 & 36: 2815 Lumens (source) Light color: 2700 K or 3500 K Color accuracy: 90+ CRI
Light output: Plura 18 & 24: 1690 Lumens (source) Plura 30 & 36: 2815 Lumens (source) Light color: 2700 K or 3500 K Color accuracy: 90+ CRI Power usage:
Light output: Plura 18 & 24: 1690 Lumens (source) Plura 30 & 36: 2815 Lumens (source) Light color: 2700 K or 3500 K Color accuracy: 90+ CRI Power usage: Plura 18 & 24: 19.5 W

GU-24 Base Specifications Light source: Plura 18 & 24: 2x GU-24 base socket Plura 30 & 36: 4x GU-24 base socket Lamping: Plura 18 & 24: 2x GU-24 base, 18 W max each Plura 30 & 36: 4x GU-24 base, 18 W max each Bulbs not included Input voltage: 300 V AC max


Suitable for a sloped ceiling Wood grain will vary Specifications subject to change

MATERIAL & FINISH OPTIONS Plura flush mount part # 08-100-

Plura flush mount part # 08-100	
	TTTT
Ø:	
18" Ø	18
24" Ø	24
30" Ø	30
36" Ø	36
Wood Body	
walnut (CM-001)	w
dark stained walnut (CM-002)	
white washed oak (CM-095)	0
a	
Shade Material	-1
frosted polymer (CM-051) matte black (CM-085)	F
with matte white interior	В
brushed aluminum (CM-012)	A
brushed rose gold (CM-046)	G
brushed brass (CM-047)	R
distressed brass (CM-096)	D
gloss white (CM-054)	w
Lamping	
2700 K LED	27
3500 K LED	35
GU-24 base sockets	GU
Driver (LED version only) 120-277 V AC input voltage	1
0-10 V dimming	
TRIAC and ELV dimming at	P1
120 V AC only	
120 V AC OTTY	Ţ



Emergency backup option available upon request Also available in a pendant version



Includes

frosted polymer (CM-051)

▲ WARNING. California Proposition 65 Warning for California Consumers. This product can expose you to chemicals including wood dust and lear or birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

distressed brass

(CM-096)



brushed aluminum

(CM-012)