## LINE WALL

# FOLIO





	5.91 X 47.24 in	5.91 x 59.06 in	5.91 x 70.87 in	3.94 x 94.49 in	3.94 x 118.11 in
ELECTRICAL SPECS.					
Voltage: Driver - transformer: Consumption P1: Consumption P2: Dimmability:	24 V DC AC/DC 24 V 26 W 53 W DMX, DALI, 1-10 V (with PWM) and Potentiometer (with PWM)	24 V DC AC/DC 24 V 33 W 66 W DMX, DALI, 1-10 V (with PWM) and Potentiometer (with PWM)	24 V DC AC/DC 24 V 40 W 80 W DMX, DALI, 1-10 V (with PWM) and Potentiometer (with PWM)	24 V DC AC/DC 24 V 53 W 106 W DMX, DALI, 1-10 V (with PWM) and Potentiometer (with PWM)	24 V DC AC/DC 24 V 66 W 132 W DMX, DALI, 1-10 V (with PWM) and Potentiometer (with PWM)
PHYSICAL SPECS.					
Thickness: Weight: Materials:	0.94 in 11.02 lb Acrylic (PMMA) - Aluminium	0.94 in 13.22 lb Acrylic (PMMA) - Aluminium	0.94 in 15.43 lb Acrylic (PMMA) - Aluminium	0.94 in 13.22 lb Acrylic (PMMA) - Aluminium	0.94 in 17.63 lb Acrylic (PMMA) - Aluminium
Size:	5.91 in	5.91 in 59.06 in	5.91 in 70.87 in	3.94 in 94.49 in	3.94 in 188.11 in
LED					
Luminous flux output P1: Luminous flux output P2: LED color temp. (CCT):	1050 lm 2000 lm 2700 K, 3000 K, 4000 K	1181 lm 2250 lm 2700 K, 3000 K, 4000 K	1299 lm 2475 lm 2700 K, 3000 K, 4000 K	1402 lm 2670 lm 2700 K, 3000 K,	1575 lm 3000 lm 2700 K, 3000 K, 4000 K
Color rendering index:	RA min. 90 - R9 min. 50	RA min. 90 - R9 min. 50	RA min. 90 - R9 min. 50	4000 K RA min. 90 - R9 min. 50	RA min. 90 - R9 min. 50
LED positioning:	One or two sides	One or two sides			
GENERAL SPECS.					
Mounting: Environment of use: Estimated LED Lifespan:	Wall lamp Indoor 50,000 hours	Wall lamp Indoor 50,000 hours	Wall lamp Indoor 50,000 hours	Wall lamp	Wall lamp
Warranty:	2 years	2 years	2 years	2 425 Peachtree Hil	ls Ave. NE #3 Atlanta, G

Cifralluminio Srl | Italia | 25135 Brescia | Via R.Gessi 10 | T +39 030 3363047 | F +38 404.876.1064

## LINE WALL




## FOLIO N N

### **TECHINCAL DESCRIPTION**

Line is the series of FOLIO® products of rectangular shape, with a thickness of 0.94 inand width between 3.94 in and 11.81 in, elegant and graceful even with a length of 118.11 in LED panels with microprism laser incision, 0.39 in opal diffuser (PMMA) and 16mm aluminum case. Single or double LED installed along the length of the panel.

#### POLAR DIAGRAM [cd/klm]



#### **APPLICATIONS**



Cifralluminio Srl | Italia | 25135 Brescia | Via R.Gessi 10 | T +39 030 3363047 | F +39