
lambert&fils

LAURENT 13



Туре	Suspension				
Materials	Sphere: Frame:	handblown opaline glass polished brass or powder coated aluminum or nickel plated steel			
	Hardware:	polished brass or powder coated aluminium			
	Wire:	nylon			
Total Height	Height to be specified upon order				
Weight	Starts at 36 lb / 16.2 kg				
Light Bulb	LED (included), 9 x 4.5W				
Sockets	G9				
Voltage	120V / 240V				
Dimmer	Refer to our recommended list of dimmer models				
Certifications	CULUSED US CE				
	Must be installed by an electrician Additional charges for modifications				

- Lead time between 7-9 weeks
- Dimensions are approximate and may vary slightly




8" / 198 mm



lambert&fils

Order Guide: SKU



CANOPY COLOR

custom color available on demand




flat black



lambert&fils

LIGHT BULB & DIMMER SPECIFICATIONS

G9 SOCKETS



Frosted 4.5W 100V-120V / 240V 450 Lumens 2700 K 25 000 H CRI ≥80 2 years warranty



DIMMER LIST COMPATIBILITY FOR G9 LED BULBS - 120V

The dimming technology offering the best results is ELV (electronic low voltage) dimmers with reverse phase or trailing edge control.

DIMMER BRAND	MODEL NUMBER	MAX LEVEL	MIN LEVEL	FLICKERING	OVERALL QUOTE
LUTRON - MAESTRO	MAELV-600	100%	0%	0%-10%	good
LUTRON - SKYLARK	SELV-300P	100%	0%	no	very good
LUTRON - SKYLARK	SELV-303P	100%	0%	no	very good
LUTRON - SKYLARK	CTELV-303P	100%	0%	no	very good
LUTRON - DIVA	DVELV-300P	100%	0%	no	very good
LEGRAND - ADORNE	TRUE UNIVERSAL	100%	30%	no	good

DIMMER LIST COMPATIBILITY FOR G9 LED BULBS - 230V

DIMMER BRAND	MODEL NUMBER	MAX LEVEL	MIN LEVEL	FLICKERING	OVERALL QUOTE
VARILIGHT	V-PRO	100%	2%	no	very good
LEGRAND - NILOÉ	3 996 35	87%	15%	no	good
NIKO	310-0280X	94%	5%	no	very good
NIKO	310-0190X	100%	1%	no	very good

*Other dimmers can yield good results and we recommend conducting your own test before final installation.

