CIRCA PENDANT

DESCRIPTION

Circa's revolutionary flat-panel LED light source combines seamless movement with warm and balanced illumination. Through its 45° shade tilt and 360° rotation, Circa redefines the ambient lighting category. Circa is available in a wide range of models to satisfy all residential, office and hospitality applications.

FIXTURE TYPE

Pendant

LIGHT SOURCE

LED Flat-Panel

LIGHT CONTROL

Hard wired, dimmable Compatible with TRIAC and ELV dimmers 0-10V dimming available upon request

FEATURES

360° shade rotation 45° shade tilt in two directions Ships flat-packed

SPECIFICATIONS

Voltage: 120 or 240V 50-60Hz Power Consumption: 10.5W Color temperature: 2700K

Luminosity: 12"(500Lm), 16"(800 Lm) Luminaire efficacy: 76 Lumens/Watt Color Rendition Index: 90 CRI

Title 20 compliant 50K hour lifespan

Cable length: 10' (305cm) (Field Cuttable)

CERTIFICATIONS





PRODUCT CODES

| PRODUCT CODES | |
|----------------------------|-----------------|
| Circa Pendant 12 Graphite: | CIRC PND 12 GPT |
| Circa Pendant 12 White: | CIRC PND 12 WHT |
| Circa Pendant 16 Graphite: | CIRC PND 16 GPT |
| Circa Pendant 16 White: | CIRC PND 16 WHT |

PACKAGING WEIGHT AND DIMENSIONS

| Circa Pendant 12: | 5.75LBS | 15" X 14" X 4" |
|--------------------|---------|--------------------|
| | 2.6KGS | 38cm X 36cm X 10cm |
| Circa Pendant 16 : | 9.05LBS | 18.5" X 18" X 4" |
| | 4.1KGS | 47cm X 46cm X 10cm |

NOTES

This lamp is not recommended for damp locations.





FINISHES



DIMENSIONS

CIRCA PENDANT 12 CIRCA PENDANT 16

