M64 MIguel MIIá. 1964 Pendant lamps





CE c@us 🕒

As a remarkable exponent of a period when Spanish design began to establish itself as a professional discipline, in 1964 this lamp was awarded the Golden Delta, the highest distinction that can be achieved by an industrial product in Spain. The jury of the prize that year was presided by prominent Swiss artist and designer Max Bill, a major proponent of the UIm school, and it is said that he championed it eloquently, vote after vote, until the final award. Accordingly, ennobled by his support a young Miguel Milá fondly referred to it as the Max Bill lamp, which ultimately came to be known as the M64.

On the occasion of the fiftieth anniversary of those events, Santa & Cole re-released it, adapting it for the HeadLed System so today it features the best light quality and efficiency. In five finishes (brilliant red, matte black or white and polished brass or aluminium) the M64 continues to embody the superb formal timelessness of the master Miguel Milá.

General description:

Capsule with LED module, translucent diffuser and heat sink with black matte finish.

5 lampshades options: polished brass, polished aluminium, white matte, black matte (exterior) or brilliant red aluminium.

5 metal circular canopy options with power supply incorporated:

Not adjustable: white recessed (CE Market) or white or black surface-mounted canopy with matte finish.

Suitable for dimming 1-10V. (Not included external dimmer switch 1-10V): white or black surface-mounted canopy with matte finish and power supply incorporated.

S&C LED capsule suitable with HeadLed System lampshades. Electric cable length: 3 m / 118.1 - 8 m / 315" Suitable for Junction Box (UL market).

Light source:

Light source included Module of 4 LEDs

Not adjustable (CE Market): Power: 3,7 W Operating current: 350 mA T^a Color: 2.700 K CRI: 90 Lifetime: 40.000 h Luminous flux: 416 Im

Adjustable: Power: 7,7 W Operating current: 700 mA T^a Colour : 2.700 K CRI: 90 Lifetime: 40.000 h Luminous flux: 752 Im Built-in LED. Suitable for dimming 1-10V. (Not included external dimmer switch 1-10V). Energy efficiency class (E.E.C): A⁺⁺... A. Suitable only for indoor use. Always use this light source.

Input voltaje : 90 ~ 305 Vac. (50 Hz / 60 Hz). According to destination.

LOR with lampshade:

- Polished brass: 68%
- Polished aluminium: 63%
- Black matte aluminium: 63%
- White matte aluminium: 69%
- Brilliant red aluminium: 63%



The technical information provided by Santa & Cole may be modified at any time without prior notice. We protect intellectual properinfo@santacole.com / +34 938 619 100 / santacole.com



Approximate weight (unpacked):

Weight with brass lampshade: 1,35 kg / 2.98 lb Weight with aluminium lampshade: 1 kg / 2.2 lb

Regulations:

CE UNE-EN 60598 UNE-EN 55015 UNE-EN 60529 UNE-EN 62031 UNE-EN 61000-3-2 UNE-EN 61347-2-13

UL

Dry and damp location UL-1598 UL-8750 E-33677

Maintenance:


Clean with a smooth cloth. Do not use ammonia, solvents or abrasive cleaning products.

Others:

The lamp is delivered in different packages.

The assembly instructions are delivered with the product.

Model: Surface canopy (sizes in cm)




Collection:

Pendant lamps



M68







The technical information provided by Santa & Cole may be modified at any time without prior notice. We protect intellectual prope info@santacole.com / +34 938 619 100 / santacole.com