

Nimba

Antoni Arola, 1997

Pendant lamp



Nimba 60




A

Nimba 90




B

Nimba 120



C

Nimba 180



D

Nimba is the first lamp designed by Antoni Arola. It is a floating ring of light formed by a metal profile that houses the light source and a lower shade to diffuse the light. Nimba is named after the halo or aureole of the holy depictions – “it can be seen but is not there” – and owing to its arrangement, the light focuses in the middle of nothing in order to spread the light in all directions.

Used in a single unit or with several, Nimba creates incorporeal, spiritual atmospheres; it illuminates in a diffused, though effective fashion and is perfect for thoroughfares and retreats. The series comprises four models of increasing diameter, all using LEDs and seamlessly fusing simplicity and high-tech.

GENERAL DESCRIPTION

Stainless steel structure with natural or gold varnish finish.

White PVC lampshade.

Black metallic circular canopy with power supply incorporated.

Electric cable length: 5 m / 196.8”

Suitable for Junction Box (UL market).

LIGHT SOURCE

(A)

Strip of 144 LEDs
Power system: 45 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 90
Lifetime: 40.000 h
Luminous flux: 1.798 lm

(B)

Strip of 192 LEDs
Power system: 65 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 90
Lifetime: 40.000 h
Luminous flux: 2.540 lm

(C)

Strip of 276 LEDs
Power system: 95 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 90
Lifetime: 40.000 h
Luminous flux: 3.713 lm

(D)

Strip of 408 LEDs
Power system: 140 W
Operating voltage: 24 VDC
T^a Colour: 2.700 K
CRI: 90
Lifetime: 40.000 h
Luminous flux: 5.550 lm

Built-in LED.

The light source for this luminaire is replaceable.

Energy efficiency class (E.E.C): A⁺⁺... A

Suitable for 1-10V / DALI

(Not included external dimmer switch 1-10V / DALI).

Fixture suitable only for indoor use.

Always use this light source.

Input voltage: 90 ~ 305* VAC
(50 Hz / 60 Hz) According to destination.

* UL Market: They have been tested with UL certification
with an input voltage (VAC) of 120 V and 277 V



SANTA & COLE



APPROXIMATE WEIGHT (unpacked)

- (A) Nimba 60: 7,4 Kg / 16.3 lb
- (B) Nimba 90: 9,5 Kg / 20.9 lb
- (C) Nimba 120: 12,6 Kg / 27.8 lb
- (D) Nimba 180: 17 Kg / 37.5 lb

REGULATIONS

CE



Class 2

IP-20

Dry location only

UNE-EN 60598

UL-1598

UNE-EN 55015

UL-8750

UNE-EN 62031

E-336377

UNE-EN 61000-3-2

UNE-EN 60529

UNE-EN 61347-2-13

MAINTENANCE

Clean with a smooth cloth. Do not use ammonia, solvents or abrasive cleaning products.

OTHERS

The lamp is delivered in different packages.

The assembly instructions



425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305
404.876.1064 sales@illumco.com

12 / 2017

nimba | Antoni Aroia | santacole.com 2/3

MODELS

