


# PRODUCT DESCRIPTION

Whether used as vanity lighting or above portraits and shelves, the Mona wall sconces are sure to illuminate a masterpiece. The tubular LED frame rotates to direct the lighting wherever it is needed. The back plate is sized for single gang junction box installs and an additional cover plate is provided for convenience. Available in either a rich burnished Gold plated finish or Matte Black powder coat, these wall lights pair well in both modern and traditional settings.



#### **MEASUREMENTS**

DIMENSION : 18.5" W x 4.25" H x 3" Ext MAX OAH : 3" W x 4.75" H

HANGING WEIGHT : 2.42 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 980 Rated (680 Del.)

BULB : 14W LED PCB Integrated, 14W Total

**BULB INCLUDED** : (Integrated) DIMMABLE : ELV or 0-10V CRI : 90 CRI COLOR\_TEMP : 3000K LIGHTING\_DIRECTION : Directional

# **FINISHES OPTION**



#### MATERIAL

Aluminum, Acrylic, Steel

#### **RATINGS**

cETLus Damp Location

ADA









## **ADDITIONAL**

INSTALL UP/DOWN: Horizontal RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.




Quantity:	Commen



# PRODUCT DESCRIPTION

Whether used as vanity lighting or above portraits and shelves, the Mona wall sconces are sure to illuminate a masterpiece. The tubular LED frame rotates to direct the lighting wherever it is needed. The back plate is sized for single gang junction box installs and an additional cover plate is provided for convenience. Available in either a rich burnished Gold plated finish or Matte Black powder coat, these wall lights pair well in both modern and traditional settings.



# **MEASUREMENTS**

DIMENSION : 30.5" W x 4.25" H x 3" Ext

MAX OAH : 3" W x 4.75" H HANGING WEIGHT : 3.52 lb

LAMPING

INPUT VOLTAGE : 120-277V

LUMENS : 1,260 Rated (900 Del.)

BULB : 18W LED PCB Integrated, 18W Total

**BULB INCLUDED** : (Integrated) DIMMABLE : ELV or 0-10V CRI : 90 CRI COLOR\_TEMP : 3000K LIGHTING\_DIRECTION : Directional

# **FINISHES OPTION**



#### MATERIAL

Aluminum, Acrylic, Steel

#### **RATINGS**

cETLus Damp Location

ADA









## **ADDITIONAL**

INSTALL UP/DOWN: Horizontal RATED LIFE 50000 Hours **OPERATING TEMPERATURE:** -20°C (-4°F), 40°C (104°F)

Always consult a qualified electrician before installing any lighting product.



	Job Name:	Job Type:
	Quantity:	Comments