

Icon 23521

project name:	
project location:	
specifier name:	
specifier location:	
quantity:	
fixture type:	

modifications:

Base Specs


14"h x 6"w x 4"d Opal Acrylic Diffuser Up to 4 custom characters included

Notes

Available w/ braille and raised number placard — ±\$ Inquire

Custom logos available — ±\$ Inquire


Marine grade primer available — ±\$ Inquire.







^{*} example of optional braille and raised character placard. (location, size, and specifics TBD)





Icon 23521

standard finish:

BA - Bronze Age

BK - Black

CB - Cast Bronze

DI - Dark Iron

NB - New Brass

SP - Satin Pewter

lamping:

02: 8.4w Integrated LED, 1181 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming (120V), or 120-277V, 0-10V Dimming (277V), UL/cUL Wet (120V Or 277V Must Be Specified)

04: 14w Integrated LED, 2198 Initial Lumens, 3000K, 90 CRI, 120V-277V, 0-10V Dimming, UL/cUL Dry/Damp

14: 8.4w Integrated LED, 1181 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming, UL/cUL Dry/ Damp

standard diffuser:

OA - Opal Acrylic



