Icon 23523

project name:	
project location:	
specifier name:	
specifier location:	
quantity:	
fixture type:	




Base Specs

12"dia. x 2.25"d. Opal Acrylic Diffuser Up to 4 custom characters included

Notes

Available with braille and raised number placard — ±\$ Inquire Custom logos available — ±\$ Inquire Marine grade primer available — ±\$ Inquire.









* example of optional braille and raised character placard. (location, size, and specifics TBD)

UltraLights The Heart of Illumination | 520.623.9829 | ultralightslighting.com



Icon 23523

standard finish:

BA - Bronze Age BK - Black CB - Cast Bronze DI - Dark Iron NB - New Brass SP - Satin Pewter

lamping:

02: 23.57w Integrated LED, 3774 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming (120V), or 120-277V, 0-10V Dimming (277V), UL/ cULWet(120V or 277V Must Be Specified)

04: 17.9w Integrated LED, 3043 Initial Lumens, 3000K, 90 CRI, 120V-277V, 0-10V Dimming, UL/cUL Dry/Damp

14: 23.57w Integrated LED, 3774 Initial Lumens, 3000K, 90 CRI, 120V, Standard Phase Dimming, UL/ cUL Dry/Damp

standard diffuser:

OA - Opal Acrylic



UltraLights The Heart of Illumination | 520.623.9829 | ultralightslighting.com

