ALPHA

Design by Ramos & Bassols.



Reference

7940.

Application

Wall Fixtures

Installation type

Surface mounted

Description

Wall lamps with on/off switch, available in matte white lacquer and chrome, matte black lacquer and chrome, matte graphite lacquer and black, and matte white lacquer. Its methacrylate diffuser gives a warm, very cozy light. Alpha follows' the reader's movements as it rotates and can be angled, opening up to 75° and turning through 360°, which also enables it to provide indirect lighting.

Diffuser

Polycarbonate diffuser

Materials

Lid: Steel

Body: Aluminum

Finishes


7940-03 White and chrome (RAL 9016)

'940-04 Black and chrome (RAL 9005)

940-18 Black and satin nickel (RAL 9005)

7940-93 White and satin mate (RAL 9016)

Sketch



Electrical characteristics

1 x LED 2.1W 700mA

Total 2.1 W





Light source: 2700K CRI >80 139 Im 66 Im/W

Driver included: CC - Constant Current 700 mA 120V 50/60Hz

Electronic dimming: NO DIMMING

Technical characteristics

- On/off switch on the front cover

Installation and assembly

Please see the installation manual


Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.



Photometric data



Certificates













ALPHA

Design by Ramos & Bassols.



Reference

7942.

Application

Wall Fixtures

Installation type

Surface mounted

Description

Wall lamps, available in matte white lacquer and chrome, matte black lacquer and chrome, matte graphite lacquer and black, and matte white lacquer. Its methacrylate diffuser gives a warm, very cozy light. Alpha follows' the reader's movements as it rotates and can be angled, opening up to 75° and turning through 360°, which also enables it to provide indirect lighting.

Diffuser

Polycarbonate diffuser

Materials

Lid: Zinc aluminum alloy Body: Aluminum

Finishes




942-04 Black and chrome (RAL 9005)

942-18 Black and satin nickel (RAL 9005)

7942-93 White and satin mate (RAL 9016)

Sketch



Electrical characteristics

1 x LED 2.1W 700mA



Total 2.1 W





Light source: 2700K CRI >80 139 lm 66 lm/W

Driver included: CC - Constant Current 700 mA 120V 50/60Hz

Electronic dimming: NO DIMMING

Installation and assembly


Please see the installation manual

Light distribution

Reading

Lamp having a light beam whose main function is to supply sufficient light for reading.





Certificates







