Halo

Design by Martin Azua.

VIBIA

Reference

2356.

Application Pendants

Installation type Surface mounted

Description

Hanging lamp. Providing an ambient or indirect light through its vertical methacrylate diffuser. The diffuser is supported by a fine grade steel structure. The back part of the diffuser in steel is finished in either a gold or graphite color lending it a clean decorative aesthetic.

Diffuser

PMMA diffuser

Materials Diffuser: Acrylic LED support: Aluminum Pendant structure: Steel Canopy: Steel

Finishes

2356-11 Black (NCS S 8500N)



Sketch



Electrical characteristics1 x LED STRIP 24V 15,3W

A⁺

Total 15.3 W



Light source: 3000K CRI >80 4584.12 lm 99.87 lm/W Fixture: 3470.39 lm 60.82 lm/W Driver included: CV - Constant Voltage 120-277V 50/60Hz

Electronic dimming: 0-10V Optional dimming: DALI Remote dimming: Lutron ECO

Technical characteristics - Surface Mounted

Installation and assembly Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Coordinate system : CG

Total flux : 3470.39 lm

Maximum value : 697.50 cd

Light position : C=180.00 G=65.00 Symmetry on the planes : Asymmetric

Efficiency : 100 %

Isolux : Floor

Light position : X=0.00m Y=0.00m Z=2.50m

Certificates



