

Halo

Design by Martin Azua.

VIBIA

Reference

2361.

Application

Wall Fixtures

Installation type

Surface mounted

Description

Wall sconce. The light rods, anchored to an aluminum profile are arranged around a central perpendicular axis, in parallel or angled. The modular character allows for large interconnected lights murals to be configured.

Diffuser

PMMA diffuser

Materials

Diffuser: Acrylic
LED support: Aluminum
Wall support: Aluminum

Finishes




2361-11 Black (NCS S 8500N)



2361-13 Grey L1 (NCS S 1000-N)

Sketch



Electrical characteristics

3 x LED STRIP 24V 15,3W

Total 45.9 W



Light source: 3000K CRI >80 4584.12 lm 99.87 lm/W

Fixture: 3472.02 lm 75.64 lm/W

Driver included: CV - Constant Voltage 120-277V 50/60Hz

Electronic dimming: NO DIMMING

Remote dimming: DALI or Lutron ECO

Technical characteristics

- Surface Mounted


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 100 %

Coordinate system : CG

Total flux : 3466.15 lm

Maximum value : 580.67 cd

Light position : C=180.00 G=70.00

Symmetry on the planes : Asymmetric

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates



 **illuminations**
425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305
404.876.1064 sales@illumco.com