Design by Diego Fortunato.



Reference

5500.

Application

Table Lamps

Installation type

Surface mounted

Description

The Mayfair lamps are a Diego Fortunato design proposal. The entire Mayfair collection incorporates LED lighting and comes in green.

Diffuser

Polycarbonate diffuser

Materials

Shade: Acrylic Diffuser: Polycarbonate Base: Aluminum

Finishes



5500-07 Matte graphite lacquer and matte green lacquer (RAL 7016, RAL 6026)

Sketch



Electrical characteristics

1 x LED STRIP 24V 2.4W AND

1 x LED STRIP 24V 12.6W

Total 15.0 W







 $\textbf{Light source:}\ 2700 \text{K CRI} > \!\!80\ 1841\ \text{Im}\ 123\ \text{Im/W}$

Fixture: 484 lm 32 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming: SENSOR

Technical characteristics

- Sensor optical dimmer
- Touch sensitive dimmer swich on base

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data









Design by Diego Fortunato.



Reference

5502.

Application

Table Lamps

Installation type

Recessed

Description

Mayfair table lamp, design by Diego Fortunato, uses new LED technology to enhance the reformed billiards light. The lamp can be dimmed via an optical sensor. The Mayfair table lamp is available in a matte graphite with green lacquer finish and is now available in a bolt down version.

Diffuser

Polycarbonate diffuser

Materials


Shade: Acrylic Diffuser: Polycarbonate Base: Zinc aluminum alloy Vertical tube: Steel

Finishes



5502-07 Matte graphite lacquer and matte green lacquer (RAL 7016, RAL 6026)

Sketch



Electrical characteristics

1 x LED STRIP 24V 2.4W

1 x LED STRIP 24V 12.6W

Total 15.0 W







Light source: 2700K CRI >80 1841 lm 116 lm/W

Fixture: 484.16 lm 30.45 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming: SENSOR

Technical characteristics

- Touch sensitive dimmer swich on base

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency: 26.31% Coordinate system : CG Total flux : 1840.50 lm

Maximum value : 66.01 cd/klm Light position: C=45.00 G=40.00 Symmetry on the planes : Asymmetric Isolux: Isolux (Floor) Light position : X=0.00m Y=0.00m Z=2.50m











Design by Diego Fortunato.



Reference

5503.

Application

Table Lamps

Installation type

Recessed

Description

Mayfair table lamp, design by Diego Fortunato, uses new LED technology to enhance the reformed billiards light. The lamp can be dimmed via an optical sensor. The Mayfair table lamp is available in a matte graphite with green lacquer finish and is now available in a bolt down version.

Diffuser

Polycarbonate diffuser

Materials

Shade: Acrylic Diffuser: Polycarbonate Base: Zinc aluminum alloy Horizontal tube: Steel

Finishes



5503-07 Matte graphite lacquer and matte green lacquer (RAL 7016, RAL 6026)

Sketch



Electrical characteristics

1 x LED STRIP 24V 2.4W

1 x LED STRIP 24V 12.6W

Total 15.0 W







Light source: 2700K CRI >80 1841 lm 116 lm/W

Fixture: 484.16 lm 30.45 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming: SENSOR

Technical characteristics

- Touch sensitive dimmer swich on base

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency: 26.31% Coordinate system : CG Total flux : 1840.50 lm

Maximum value : 66.01 cd/klm Light position: C=45.00 G=40.00 Symmetry on the planes : Asymmetric Isolux: Isolux (Floor) Light position : X=0.00m Y=0.00m Z=2.50m











Design by Diego Fortunato.



×

Reference

5505.

Application

Table Lamps

Installation type

Surface mounted

Description

The Mayfair lamps are a Diego Fortunato design proposal. The entire Mayfair collection incorporates LED lighting and comes in various finishes: white, black, gold and copper.

Diffuser

Polycarbonate diffuser

Materials

Shade: Steel

Diffuser: Polycarbonate Base: Aluminum

Finishes



5505-18 Graphite (Mayfair RAL 7016)



5505-20 Gold (Mayfair gold)



5505-67 Matt copper (Mayfair copper brown)



5505-93 White (Mayfair RAL 9016)

Sketch



Electrical characteristics

1 x LED STRIP 24V 2.4W

AND

1 x LED STRIP 24V 12.6W

Total 15.0 W

×



Light source: 2700K CRI >80 1841 lm 123 lm/W

Fixture: 484 lm 32 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming: SENSOR

Technical characteristics

- Sensor optical dimmer
- Touch sensitive dimmer swich on base

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data











Design by Diego Fortunato.



Reference

5507.

Application

Table Lamps

Installation type

Recessed

Description

Mayfair table lamp, design by Diego Fortunato, uses new LED technology to enhance the reformed billiards light. The lamp can be dimmed via an optical sensor. The Mayfair table lamp is available in four different finishes and is now available in a bolt down version.

Diffuser

Polycarbonate diffuser

Materials

Shade: Steel

Diffuser: Polycarbonate Base: Zinc aluminum alloy Horizontal tube: Steel

Finishes



5507-18 Graphite (RAL 7016)



5507-20 Gold (Gold)




5507-67 Matt copper (Mayfair copper brown)



5507-93 White (RAL 9016)

Sketch



Electrical characteristics

1 x LED STRIP 24V 2.4W

AND

1 x LED STRIP 24V 12.6W

Total 15.0 W





Light source: 2700K CRI >80 1841 lm 116 lm/W

Fixture: 484.16 lm 30.45 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming: SENSOR

Technical characteristics

- Touch sensitive dimmer swich on base

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency: 22.66% Coordinate system : CG

Total flux: 1840.50 lm Maximum value : 68.63 cd/klm

Light position : C=45.00 G=40.00 Symmetry on the planes : Asymmetric Isolux: Isolux (Floor) Light position :

×

X=0.00m Y=0.00m Z=2.50m











Design by Diego Fortunato.



Reference

5508.

Application

Table Lamps

Installation type

Recessed

Description

Mayfair table lamp, design by Diego Fortunato uses new LED technology to enhance the reformed billiards light. The lamp can be dimmed via an optical sensor. The Mayfair table lamp is available in four different finishes and is now available in a bolt down version.

Diffuser

Polycarbonate diffuser

Materials

Shade: Steel

Diffuser: Polycarbonate Base: Zinc aluminum alloy Horizontal tube: Steel

Finishes



5508-18 Graphite (RAL 7016)



5508-20 Gold (Gold)




5508-67 Matt copper (Mayfair copper brown)



5508-93 White (RAL 9016)

Sketch



Electrical characteristics

1 x LED STRIP 24V 2.4W

AND

1 x LED STRIP 24V 12.6W

Total 15.0 W





Light source: 2700K CRI >80 1841 lm 116 lm/W

Fixture: 484.16 lm 30.45 lm/W

Driver included: CV - Contant Voltage 100-240V 50/60Hz

Electronic dimming: SENSOR

Technical characteristics

- Touch sensitive dimmer swich on base

Installation and assembly

Please see the installation manual

Light distribution

Indirect lighting

Lamp that emits an upward or backward beam that is reflected by the ceiling or wall.



Photometric data

Efficiency: 22.66% Coordinate system : CG Total flux: 1840.50 lm

Maximum value : 68.63 cd/klm

Light position : C=45.00 G=40.00 Symmetry on the planes : Asymmetric Isolux: Isolux (Floor) Light position :

×

X=0.00m Y=0.00m Z=2.50m









