

Tempo

Design by Lieve Altherr.

Reference

5763.

Application

Wall Fixtures

Installation type

Recessed

Description

Fusing technology, space, and architecture, Sticks offers a creative lighting toolkit for integrating light elements in an interior space. Pure and graphic, the minimalist aluminium rods transform linear light into a floating sculpture.




Diffuser

Blown-glass diffuser


Materials

Body: Steel
Diffuser: Blown-glass
LED support: Aluminum

Finishes

-  **5763-18** Graphite (ADAPTA RF 9913 WX)
-  **5763-35** Brick (NCS S 4040-Y70R)
-  **5763-62** Green (NCS S 3010-G20Y)

Sketch



Electrical characteristics

1 x LED 4W 350mA

Total 4.0 W



VIBIA



Light source: 2700K CRI >90 440.81 lm 110 lm/W

Fixture: 301.62 lm 75.4 lm/W

Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or TRIAC

Technical characteristics

- Recessed


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 100%

Coordinate system : CG

Total flux : 301.62 lm

Maximum value : 235.37 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates



 **illuminaTions**

425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305
404.876.1064 sales@illumco.com