Design by Lievore Altherr.

VIBIA

Reference

5772.

Application Pendants

Installation type Surface mounted

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blown-glass diffuser

Materials LED support: Aluminum Diffuser: Blown-glass

Canopy: Steel



5772-18 Graphite (ADAPTA RF 9913 WX)

5772-35 Brick (NCS S 4040-Y70R)

5772-62 Green (NCS S 3010-G20Y)

Sketch

Electrical characteristics 1 x LED 4W 350mA

(ē)

A⁺⁺



Total 4.0 W





Light source: 2700K CRI >90 440.81 lm 110 lm/W Fixture: 292 lm 73 lm/W Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V Optional dimming: TRIAC or DALI or Lutron ECO

Installation and assembly Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates





Design by Lievore Altherr.

Reference

5774.

Application Pendants

Installation type Surface mounted

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blown-glass diffuser

Materials LED support: Aluminum Diffuser: Blown-glass Canopy: Steel



5774-18 Graphite (ADAPTA RF 9913 WX)

5774-35 Brick (NCS S 4040-Y70R)

5774-62 Green (NCS S 3010-G20Y)

Sketch



Certificates



Electrical characteristics

1 x LED 4W 350mA (ē)



Total 4.0 W





Light source: 2700K CRI >90 440.81 Im 110 Im/W Fixture: 302.04 Im 75.4 Im/W Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V Optional dimming: TRIAC or DALI or Lutron ECO

Installation and assembly Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data



Design by Lievore Altherr.

VIBIA

Reference

5776.

Application Pendants

Installation type Surface mounted

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blown-glass diffuser

Materials LED support: Aluminum Diffuser: Blown-glass Canopy: Steel


Finishes

5776-18 Graphite (ADAPTA RF 9913 WX)

5776-35 Brick (NCS S 4040-Y70R)

5776-62 Green (NCS S 3010-G20Y)

Sketch



Certificates





1 x LED 4W 350mA



Total 4.0 W





Light source: 2700K CRI >90 440.81 lm 110 lm/W Fixture: 317 lm 79 lm/W Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V Optional dimming: TRIAC or DALI or Lutron ECO

Installation and assembly Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Design by Lievore Altherr.

Reference

5778.

Application Pendants

Installation type Surface mounted

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blown-glass diffuser

Materials LED support: Aluminum Diffuser: Blown-glass Canopy: Steel

Finishes

5778-18 Graphite (ADAPTA RF 9913 WX)

5778-35 Brick (NCS S 4040-Y70R)

5778-62 Green (NCS S 3010-G20Y)

Sketch



Electrical characteristics 1 x LED 4W 350mA


(ē)

A⁺⁺

Photometric data



Total 4.0 W





Light source: 2700K CRI >90 440.81 Im 110 Im/W Fixture: 261 Im 65 Im/W Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V Optional dimming: TRIAC or DALI or Lutron ECO

Installation and assembly Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Certificates





Design by Lievore Altherr.

Reference

5780.

Application Pendants

Installation type Surface mounted

Description

Tempo pendant lamps are a design by Lievore Altherr. Suspended from the cable, the blown glass diffuser offers subtle nuances of transparency and translucency. All models of the Tempo collection incorporate LED lighting.

Diffuser

Blown-glass diffuser

Materials LED support: Aluminum Diffuser: Blown-glass Canopy: Steel

Finishes

5780-18 Graphite (ADAPTA RF 9913 WX)

5780-35 Brick (NCS S 4040-Y70R)

5780-62 Green (NCS S 3010-G20Y)

Sketch



Certificates







Light source: 2700K CRI >90 440.81 Im 110 Im/W Fixture: 280.99 Im 70.24 Im/W Driver included: CC - Constant Current 350 mA 120-277V 50/60Hz

Electronic dimming: 0-10V Optional dimming: TRIAC or DALI or Lutron ECO

Installation and assembly Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data



Electrical characteristics

1 x LED 4W 350mA (ē)



Total 4.0 W

