

TUBE

Design by Ichiro Iwasaki.

Reference

6100.

Application

Ceiling Fixtures

Installation type

Surface mounted

Description

Ceiling lamp defined by its curved sheet aluminum shade lending a visual and material lightweight quality. Size selection from 11 1/4 to 20 1/2 in diameters with 4 different finishes, white and three greys.

Diffuser

Polycarbonate diffuser


Materials

LED support: Aluminum

Canopy: Steel

Finishes


 **6100-10** White (NCS S 0300-N)

 **6100-15** Grey L2 (NCS S 2500-N)

 **6100-16** Grey M1 (NCS S 4500-N)

 **6100-21** Grey D1 (NCS S 7000-N)

Sketch



Electrical characteristics

1 x LED PLATE 13.5W 700mA

Total 13.5 W



VIBIA



Light source: 2700K CRI >90 1740 lm 128.8 lm/W

Fixture: 632 lm 46.81 lm/W

Driver included: CC - Constant Current 700 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or Lutron ECO

Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 39.65 lm/W

Coordinate system : CG

Total flux : 631.96 lm

Maximum value : 259.67 cd

Light position : C=0.00 G=0.00

Symmetry on the planes : Double symmetrical

Isolux : Floor

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates





425 Peachtree Hills Ave. NE #3 Atlanta, GA 30305
404.876.1064 sales@illumco.com

TUBE

Design by Ichiro Iwasaki.

Reference

6105.

Application

Ceiling Fixtures

Installation type

Surface mounted

Description

Ceiling lamp defined by its curved sheet aluminum shade lending a visual and material lightweight quality. Size selection from 11 1/4 to 20 1/2 in diameters with 4 different finishes, white and three greys.

Diffuser


Polycarbonate diffuser

Materials

LED support: Aluminum
Canopy: Steel

Finishes


 **6105-10** White (NCS S 2500-N)

 **6105-15** Grey L2 (NCS S 2500-N)

 **6105-16** Grey M1 (NCS S 4500-N)

 **6105-21** Grey D1 (NCS S 7000-N)

Sketch



Electrical characteristics

1 x LED PLATE 20W 700mA

Total 20.0 W



VIBIA



Light source: 2700K CRI >90 2900 lm 145 lm/W

Fixture: 1169.9 lm 58.49 lm/W

Driver included: CC - Constant Current 700 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or Lutron ECO

Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates



TUBE

Design by Ichiro Iwasaki.

Reference

6110.

Application

Ceiling Fixtures

Installation type

Surface mounted

Description

Ceiling lamp defined by its curved sheet aluminum shade lending a visual and material lightweight quality. Size selection from 11 1/4 to 20 1/2 in diameters with 4 different finishes, white and three greys.

Diffuser

Polycarbonate diffuser

Materials

LED support: Aluminum

Canopy: Steel

Finishes


 **6110-10** White (NCS S 0300-N)

 **6110-15** Grey L2 (NCS S 2500-N)

 **6110-16** Grey M1 (NCS S 4500-N)

 **6110-21** Grey D1 (NCS S 7000-N)

Sketch



Electrical characteristics

1 x LED PLATE 20W 700mA

Total 20.0 W



VIBIA



Light source: 2700K CRI >90 2900 lm 145 lm/W

Fixture: 1169.9 lm 58.49 lm/W

Driver included: CC - Constant Current 700 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or Lutron ECO

Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Certificates

